

System.Single Structure

```
[ILAsm]
.class public sequential sealed serializable Single extends
System.ValueType implements System.IComparable, System.IFormattable,
System.IComparable`1<float32>, System.IEquatable`1<float32>

[C#]
public struct Single: IComparable, IFormattable, IComparable<Single>,
IEquatable<Single>
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- **System.IComparable**
- **System.IFormattable**
- **System.IComparable<System.Single>**
- **System.IEquatable<System.Single>**

Summary

Represents a 32-bit single-precision floating-point number.

Inherits From: System.ValueType

Library: ExtendedNumerics

Thread Safety: All public static members of this type are safe for multithreaded operations. No instance members are guaranteed to be thread safe.

Description

`System.Single` is a 32-bit single precision floating-point type that represents values ranging from approximately 1.5E-45 to 3.4E+38 and from approximately -1.5E-45 to -3.4E+38 with a precision of 7 decimal digits. The `System.Single` type conforms to standard IEC 60559:1989, Binary Floating-point Arithmetic for Microprocessor Systems.

A `System.Single` can represent the following values:

- 1 • The finite set of non-zero values of the form $s * m * 2^e$, where s is 1 or -1, and $0 < m < 2^{24}$ and $-149 \leq e \leq 104$.
- 2
- 3 • Positive infinity and negative infinity. Infinities are produced by operations that
- 4 produce results with a magnitude greater than that which can be represented by a
- 5 `System.Single`, such as dividing a non-zero number by zero. For example, using
- 6 `System.Single` operands, `1.0 / 0.0` yields positive infinity, and `-1.0 / 0.0` yields
- 7 negative infinity. Operations include passing parameters and returning values.
- 8 • The *Not-a-Number* value (NaN). NaN values are produced by invalid floating-point
- 9 operations, such as dividing zero by zero.

10 When performing binary operations, if one of the operands is a floating-point type
 11 (`System.Double` or `System.Single`), then the other operand is required to be an integral
 12 type or a floating-point type and the operation is evaluated as follows:

- 13 • If one of the operands is of an integral type, then that operand is converted to the
- 14 floating-point type of the other operand.
- 15 • Then, if either of the operands is of type `System.Double`, the other operand is
- 16 converted to `System.Double`, and the operation is performed using at least the range
- 17 and precision of the `System.Double` type. For numeric operations, the type of the
- 18 result is `System.Double`.
- 19 • Otherwise, the operation is performed using at least the range and precision of the
- 20 `System.Single` type and, for numeric operations, the type of the result is
- 21 `System.Single`.

22 The floating-point operators, including the assignment operators, do not throw exceptions.
 23 Instead, in exceptional situations, the result of a floating-point operation is zero, infinity, or
 24 NaN, as described below:

- 25 • If the result of a floating-point operation is too small for the destination format, the
- 26 result of the operation is zero.
- 27 • If the magnitude of the result of a floating-point operation is too large for the
- 28 destination format, the result of the operation is positive infinity or negative infinity.
- 29 • If a floating-point operation is invalid, the result of the operation is NaN.
- 30 • If one or both operands of a floating-point operation are NaN, the result of the
- 31 operation is NaN.

32 Conforming implementations of the CLI are permitted to perform floating-point operations
 33 using a precision that is higher than that required by the `System.Single` type. For example,
 34 hardware architectures that support an "extended" or "long double" floating-point type with
 35 greater range and precision than the `System.Single` type could implicitly perform all
 36 floating-point operations using this higher precision type. Expressions evaluated using a
 37 higher precision might cause a finite result to be produced instead of an infinity.

Single.Epsilon Field

[ILAsm]

```
.field public static literal float32 Epsilon = (float)1.401298E-45
```

[C#]

```
public const float Epsilon = (float)1.401298E-45
```

Summary

Represents the smallest positive `System.Single` value greater than zero.

Description

The value of this constant is 1.401298E-45.

Single.MaxValue Field

```
[ILAsm]  
.field public static literal float32 MaxValue = (float)3.402823E+38  
  
[C#]  
public const float MaxValue = (float)3.402823E+38
```

Summary

Contains the maximum positive value for the `System.Single` type.

Description

The value of this constant is 3.40282346638528859E+38 converted to `System.Single`.

Single.MinValue Field

```
[ILAsm]  
.field public static literal float32 MinValue = (float)-3.402823E+38  
  
[C#]  
public const float MinValue = (float)-3.402823E+38
```

Summary

Contains the minimum (most negative) value for the `System.Single` type.

Description

The value of this constant is -3.40282346638528859E+38 converted to `System.Single`.

Single.NaN Field

```
[ILAsm]  
.field public static literal float32 NaN = (float)0.0 / (float)0.0  
  
[C#]  
public const float NaN = (float)0.0 / (float)0.0
```

Summary

Represents an undefined result of operations involving `System.Single`.

Description

Not-a-Number (NaN) values are returned when the result of a `System.Single` operation is undefined.

A NaN value is not equal to any other value, including another NaN value.

The value of this field is obtained by dividing `System.Single` zero by zero.

[*Note:* `System.Single.NaN` represents one of many possible NaN values. To test whether a `System.Single` value is a NaN, use the `System.Single.IsNaN` method.]

Single.NegativeInfinity Field

```
[ILAsm]  
.field public static literal float32 NegativeInfinity = (float)-1.0 /  
(float)0.0  
  
[C#]  
public const float NegativeInfinity = (float)-1.0 / (float)0.0
```

Summary

Represents a negative infinity of type `System.Single`.

Description

The value of this constant can be obtained by dividing a negative `System.Single` by zero.

[*Note:* To test whether a `System.Single` value is a negative infinity value, use the `System.Single.IsNegativeInfinity` method.]

Single.PositiveInfinity Field

```
[ILAsm]  
.field public static literal float32 PositiveInfinity = (float)1.0 /  
(float)0.0  
  
[C#]  
public const float PositiveInfinity = (float)1.0 / (float)0.0
```

Summary

Represents a positive infinity of type `System.Single`.

Description

The value of this constant can be obtained by dividing a positive `System.Single` by zero.

[*Note:* To test whether a `System.Single` value is a positive infinity value, use the `System.Single.IsPositiveInfinity` method.]

Single.CompareTo(System.Single) Method

```
[ILAsm]  
.method public final hidebysig virtual int32 CompareTo(float32 value)  
  
[C#]  
public int CompareTo(float value)
```

Summary

Returns the sort order of the current instance compared to the specified `System.Single`.

Parameters

Parameter	Description
<i>value</i>	The <code>System.Single</code> to compare to the current instance.

Return Value

The return value is a negative number, zero, or a positive number reflecting the sort order of the current instance as compared to *value*. For non-zero return values, the exact value returned by this method is unspecified. The following table defines the return value:

Return Value	Description
Any negative number	Current instance < <i>value</i> . -or- Current instance is a NaN and <i>value</i> is not a NaN.
Zero	Current instance == <i>value</i> . -or- Current instance and <i>value</i> are both NaN, positive infinity, or negative infinity.
A positive number	Current instance > <i>value</i> .

	-or- Current instance is not a NaN and <i>value</i> is a NaN.
--	--

1

2 **Description**

3 [Note: This method is implemented to support the `System.IComparable<Single>`
4 interface.]

5

6

7

Single.CompareTo(System.Object) Method

```
[ILAsm]  
.method public final hidebysig virtual int32 CompareTo(object value)  
  
[C#]  
public int CompareTo(object value)
```

Summary

Returns the sort order of the current instance compared to the specified `System.Object`.

Parameters

Parameter	Description
<i>value</i>	The <code>System.Object</code> to compare to the current instance.

Return Value

The return value is a negative number, zero, or a positive number reflecting the sort order of the current instance as compared to *value*. For non-zero return values, the exact value returned by this method is unspecified. The following table defines the return value:

Return Value	Description
Any negative number	Current instance < <i>value</i> . -or- Current instance is a NaN and <i>value</i> is not a NaN and is not a null reference.
Zero	Current instance == <i>value</i> . -or- Current instance and <i>value</i> are both NaN, positive infinity, or negative infinity.

A positive number	Current instance > <i>value</i> .
	-or-
	<i>value</i> is a null reference.
	-or-
	Current instance is not a NaN and <i>value</i> is a NaN.

1

2 Description

3 [Note: This method is implemented to support the `System.IComparable` interface. Note
4 that, although a NaN is not considered to be equal to another NaN (even itself), the
5 `System.IComparable` interface requires that `A.CompareTo(A)` return zero.]

6

8 Exceptions

9

10

Exception	Condition
System.ArgumentException	<i>value</i> is not a null reference and is not of type <code>System.Single</code> .

11

12

13

Single.Equals(System.Object) Method

```
[ILAsm]  
.method public hidebysig virtual bool Equals(object obj)  
  
[C#]  
public override bool Equals(object obj)
```

Summary

Determines whether the current instance and the specified `System.Object` represent the same type and value.

Parameters

Parameter	Description
<i>obj</i>	The <code>System.Object</code> to compare to the current instance.

Return Value

`true` if *obj* represents the same type and value as the current instance, otherwise `false`. If *obj* is a null reference or is not an instance of `System.Single`, returns `false`. If either *obj* or the current instance is a NaN and the other is not, returns `false`. If *obj* and the current instance are both NaN, positive infinity, or negative infinity, returns `true`.

Description

[Note: This method overrides `System.Object.Equals`.]

Single.Equals(System.Single) Method

```
[ILAsm]  
.method public hidebysig virtual bool Equals(float32 obj)  
  
[C#]  
public override bool Equals(float obj)
```

Summary

Determines whether the current instance and the specified `System.Single` represent the same value.

Parameters

Parameter	Description
<i>obj</i>	The <code>System.Single</code> to compare to the current instance.

Return Value

`true` if *obj* represents the same value as the current instance, otherwise `false`. If either *obj* or the current instance is a NaN and the other is not, returns `false`. If *obj* and the current instance are both NaN, positive infinity, or negative infinity, returns `true`.

Description

[*Note:* This method is implemented to support the `System.IEquatable<Single>` interface.]

Single.GetHashCode() Method

```
[ILAsm]  
.method public hidebysig virtual int32 GetHashCode()  
  
[C#]  
public override int GetHashCode()
```

Summary

Generates a hash code for the current instance.

Return Value

A `System.Int32` containing the hash code for this instance.

Description

The algorithm used to generate the hash code is unspecified.

[*Note:* This method overrides `System.Object.GetHashCode()`.]

Single.IsInfinity(System.Single) Method

```
[ILAsm]  
.method public hidebysig static bool IsInfinity(float32 f)  
  
[C#]  
public static bool IsInfinity(float f)
```

Summary

Determines whether the specified `System.Single` represents an infinity, which can be either positive or negative.

Parameters

Parameter	Description
<i>f</i>	The <code>System.Single</code> to be checked.

Return Value

true if *f* represents a positive or negative infinity value; otherwise false.

Description

[*Note:* Floating-point operations return positive or negative infinity values to signal an overflow condition.]

Single.IsNaN(System.Single) Method

```
[ILAsm]  
.method public hidebysig static bool IsNaN(float32 f)  
  
[C#]  
public static bool IsNaN(float f)
```

Summary

Determines whether the value of the specified `System.Single` is undefined (Not-a-Number).

Parameters

Parameter	Description
<i>f</i>	The <code>System.Single</code> to be checked.

Return Value

true if *f* represents a NaN value; otherwise false.

Description

[*Note:* Floating-point operations return NaN values to signal that the result of the operation is undefined. For example, dividing (Single) 0.0 by 0.0 results in a NaN value.]

Single.IsNegativeInfinity(System.Single)

Method

```
[ILAsm]  
.method public hidebysig static bool IsNegativeInfinity(float32 f)  
  
[C#]  
public static bool IsNegativeInfinity(float f)
```

Summary

Determines whether the specified `System.Single` represents a negative infinity value.

Parameters

Parameter	Description
<i>f</i>	The <code>System.Single</code> to be checked.

Return Value

true if *f* represents a negative infinity value; otherwise false.

Description

[*Note:* Floating-point operations return negative infinity values to signal an overflow condition.]

Single.IsPositiveInfinity(System.Single)

Method

```
[ILAsm]  
.method public hidebysig static bool IsPositiveInfinity(float32 f)  
  
[C#]  
public static bool IsPositiveInfinity(float f)
```

Summary

Determines whether the specified `System.Single` represents a positive infinity value.

Parameters

Parameter	Description
<i>f</i>	The <code>System.Single</code> to be checked.

Return Value

true if *f* represents a positive infinity value; otherwise false.

Description

[*Note:* Floating-point operations return positive infinity values to signal an overflow condition.]

Single.Parse(System.String) Method

```
[ILAsm]  
.method public hidebysig static float32 Parse(string s)  
  
[C#]  
public static float Parse(string s)
```

Summary

Returns the specified `System.String` converted to a `System.Single` value.

Parameters

Parameter	Description
s	A <code>System.String</code> containing the value to convert. The string is interpreted using the <code>System.Globalization.NumberStyles.Float</code> and/or <code>System.Globalization.NumberStyles.AllowThousands</code> style.

Return Value

The `System.Single` value obtained from s. If s equals `System.Globalization.NumberFormatInfo.NaNSymbol`, this method returns `System.Single.NaN`.

Description

This version of `System.Single.Parse` is equivalent to `System.Single.Parse(s, System.Globalization.NumberStyles.Float | System.Globalization.NumberStyles.AllowThousands, null)`.

The string s is parsed using the formatting information in a `System.Globalization.NumberFormatInfo` initialized for the current system culture.

[*Note:* For more information, see `System.Globalization.NumberFormatInfo.CurrentInfo`.]

Exceptions

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.FormatException	s is not in the correct style.
System.OverflowException	s represents a value that is less than <code>System.Single.MinValue</code> or greater than <code>System.Single.MaxValue</code> .

1
2
3

Single.Parse(System.String, System.Globalization.NumberStyles) Method

```
[ILAsm]  
.method public hidebysig static float32 Parse(string s, valuetype  
System.Globalization.NumberStyles style)  
  
[C#]  
public static float Parse(string s, NumberStyles style)
```

Summary

Returns the specified `System.String` converted to a `System.Single` value.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> containing the value to convert. The string is interpreted using the style specified by <i>style</i> .
<code>style</code>	Zero or more <code>System.Globalization.NumberStyles</code> values that specify the style of <i>s</i> . Specify multiple values for <i>style</i> using the bitwise OR operator. If <i>style</i> is a null reference, the string is interpreted using the <code>System.Globalization.NumberStyles.Float</code> and <code>System.Globalization.NumberStyles.AllowThousands</code> styles.

Return Value

The `System.Single` value obtained from *s*. If *s* equals `System.Globalization.NumberFormatInfo.NaNSymbol`, this method returns `System.Single.NaN`.

Description

This version of `System.Single.Parse` is equivalent to `System.Single.Parse(s, style, null)`.

The string *s* is parsed using the formatting information in a `System.Globalization.NumberFormatInfo` initialized for the current system culture.

[*Note:* For more information, see `System.Globalization.NumberFormatInfo.CurrentInfo`.]

Exceptions

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.FormatException	s is not in the correct style.
System.OverflowException	s represents a value that is less than <code>System.Single.MinValue</code> or greater than <code>System.Single.MaxValue</code> .

Single.Parse(System.String, System.IFormatProvider) Method

```
[ILAsm]  
.method public hidebysig static float32 Parse(string s, class  
System.IFormatProvider provider)  
  
[C#]  
public static float Parse(string s, IFormatProvider provider)
```

Summary

Returns the specified `System.String` converted to a `System.Single` value.

Parameters

Parameter	Description
<code>s</code>	A <code>System.String</code> containing the value to convert. The string is interpreted using the <code>System.Globalization.NumberStyles.Float</code> and/or <code>System.Globalization.NumberStyles.AllowThousands</code> style.
<code>provider</code>	A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> containing culture-specific formatting information about <code>s</code> .

Return Value

The `System.Single` value obtained from `s`. If `s` equals `System.Globalization.NumberFormatInfo.NaNSymbol`, this method returns `System.Single.NaN`.

Description

This version of `System.Single.Parse` is equivalent to `System.Single.Parse(s, System.Globalization.NumberStyles.Float | System.Globalization.NumberStyles.AllowThousands, provider)`.

The string `s` is parsed using the culture-specific formatting information from the `System.Globalization.NumberFormatInfo` instance supplied by `provider`. If `provider` is null or a `System.Globalization.NumberFormatInfo` cannot be obtained from `provider`, the formatting information for the current system culture is used.

Exceptions

Exception	Condition
System.ArgumentNullException	s is a null reference.
System.FormatException	s is not in the correct style.
System.OverflowException	s represents a value that is less than <code>System.Single.MinValue</code> or greater than <code>System.Single.MaxValue</code> .

Single.Parse(System.String, System.Globalization.NumberStyles, System.IFormatProvider) Method

```
[ILAsm]  
.method public hidebysig static float32 Parse(string s, valuetype  
System.Globalization.NumberStyles style, class System.IFormatProvider  
provider)  
  
[C#]  
public static float Parse(string s, NumberStyles style, IFormatProvider  
provider)
```

Summary

Returns the specified `System.String` converted to a `System.Single` value.

Parameters

Parameter	Description
<i>s</i>	A <code>System.String</code> containing the value to convert. The string is interpreted using the style specified by <i>style</i> .
<i>style</i>	Zero or more <code>System.Globalization.NumberStyles</code> values that specify the style of <i>s</i> . Specify multiple values for <i>style</i> using the bitwise OR operator. If <i>style</i> is a null reference, the string is interpreted using the <code>System.Globalization.NumberStyles.Float</code> and <code>System.Globalization.NumberStyles.AllowThousands</code> styles.
<i>provider</i>	A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> containing culture-specific formatting information about <i>s</i> .

Return Value

The `System.Single` value obtained from *s*. If *s* equals `System.Globalization.NumberFormatInfo.NaNString`, this method returns NaN.

Description

The string *s* is parsed using the culture-specific formatting information from the `System.Globalization.NumberFormatInfo` instance supplied by *provider*. If *provider* is null or a `System.Globalization.NumberFormatInfo` cannot be obtained from *provider*, the formatting information for the current system culture is used.

Exceptions

Exception	Condition
System.ArgumentNullException	<i>s</i> is a null reference.
System.FormatException	<i>s</i> is not in the correct style.
System.OverflowException	<i>s</i> represents a value that is less than <code>System.Single.MinValue</code> or greater than <code>System.Single.MaxValue</code> .

Single.ToString(System.String, System.IFormatProvider) Method

```
[ILAsm]
.method public final hidebysig virtual string ToString(string format,
class System.IFormatProvider provider)

[C#]
public string ToString(string format, IFormatProvider provider)
```

Summary

Returns a `System.String` representation of the value of the current instance.

Parameters

Parameter	Description
<i>format</i>	A <code>System.String</code> containing a character that specifies the format of the returned string, optionally followed by a non-negative integer that specifies the precision of the number in the returned <code>System.String</code> .
<i>provider</i>	A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> instance containing culture-specific formatting information.

Return Value

A `System.String` representation of the current instance formatted as specified by *format*. The string takes into account the information in the `System.Globalization.NumberFormatInfo` instance supplied by *provider*.

Description

If *provider* is null or a `System.Globalization.NumberFormatInfo` cannot be obtained from *provider*, the formatting information for the current system culture is used.

If *format* is a null reference, the general format specifier "G" is used.

The following table lists the *format* characters that are valid for the `System.Single` type.

Format Characters	Description
"C", "c"	Currency format.
"E", "e"	Exponential notation format.
"F", "f"	Fixed-point format.
"G", "g"	General format.
"N", "n"	Number format.
"P", "p"	Percent format.
"R", "r"	Round-trip format.

[*Note:* For a detailed description of the format strings, see the `System.IFormattable` interface.

This method is implemented to support the `System.IFormattable` interface.

]

Exceptions

Exception	Condition
System.FormatException	<i>format</i> is invalid.

Single.ToString(System.IFormatProvider)

Method

```
[ILAsm]  
.method public final hidebysig virtual string ToString(class  
System.IFormatProvider provider)  
  
[C#]  
public string ToString(IFormatProvider provider)
```

Summary

Returns a `System.String` representation of the value of the current instance.

Parameters

Parameter	Description
<i>provider</i>	A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> containing culture-specific formatting information.

Return Value

A `System.String` representation of the current instance formatted using the general format specifier, ("G"). The string takes into account the formatting information in the `System.Globalization.NumberFormatInfo` instance supplied by *provider*.

Description

This version of `System.Single.ToString` is equivalent to `System.Single.ToString(null, provider)`.

If *provider* is `null` or a `System.Globalization.NumberFormatInfo` cannot be obtained from *provider*, the formatting information for the current system culture is used.

[*Note:* The general format specifier formats the number in either fixed-point or exponential notation form. For a detailed description of the general format, see the `System.IFormattable` interface.]

Single.ToString() Method

```
[ILAsm]  
.method public hidebysig virtual string ToString()  
  
[C#]  
public override string ToString()
```

Summary

Returns a `System.String` representation of the value of the current instance.

Return Value

A `System.String` representation of the current instance formatted using the general format specifier, ("G"). The string takes into account the current system culture.

Description

This version of `System.Single.ToString` is equivalent to `System.Single.ToString (null, null)`.

[*Note:* The general format specifier formats the number in either fixed-point or exponential notation form. For a detailed description of the general format, see the `System.IFormattable` interface.

This method overrides `System.Object.ToString`.

]

Single.ToString(System.String) Method

```
[ILAsm]  
.method public hidebysig instance string ToString(string format)  
  
[C#]  
public string ToString(string format)
```

Summary

Returns a `System.String` representation of the value of the current instance.

Parameters

Parameter	Description
<i>format</i>	A <code>System.String</code> that specifies the format of the returned string. [<i>Note:</i> For a list of valid values, see <code>System.Single.ToString (System.String, System.IFormatProvider)</code> .]

Return Value

A `System.String` representation of the current instance formatted as specified by *format*. The string takes into account the current system culture.

Description

This version of `System.Single.ToString` is equivalent to `System.Single.ToString (format, null)`.

If *format* is a null reference, the general format specifier "G" is used.

Exceptions

Exception	Condition
System.FormatException	<i>format</i> is invalid.

Example

The following example shows the effects of various formats on the string returned by `System.Single.ToString`.

[C#]

```
using System;
class test {
    public static void Main() {
        float f = 1234.567f;
        Console.WriteLine(f);
        string[] fmts = {"C", "E", "e5", "F", "G", "N", "P", "R"};
        for (int i=0;i<fmts.Length;i++)
            Console.WriteLine("{0}: {1}",
                fmts[i],f.ToString(fmts[i]));
    }
}
```

The output is

```
1234.567
C: $1,234.57
E: 1.234567E+003
e5: 1.23457e+003
F: 1234.57
G: 1234.567
N: 1,234.57
P: 123,456.70 %
R: 1234.567
```

